



SPECIFICATION

For

SWITCHING POWER SUPPLY

M/N: MPI-815H

Revision Index

REV.	Dec. 20 th 2007	Adding index page and correct typing error from “convention” to “convection”.
REV.	Feb. 14 th 2008	OVP from 5.4-5.85V to 7V max.
REV.	Jun. 24 th 2008	Remove the tautological Hold Up Time in section 5.
REV.	Apr. 8 th 2009	Updating mechanical dimension (Height).



FEATURES

- 150W with active PFC convection cooled for P4 application
- Power Good/Power Fail signal.
- +5V Stand by & Remote On/Off
- MTBF>130,000 hr. MIL-217F at 50 degree.
- Thermal protection.

1. Description

MPI-815H is a 150W ATX power supply with active PFC for industrial and embedded system application. The device utilizes a thermally efficient U channel chassis design. Design to be convection cooled.

Output Voltage	Mini. Output Current	Rated Output Current	Max output Current ^(Note 1)	Line Regulation	Load Regulation	Ripple & Noise p-p ^(Note 2)	Initial Setting Accuracy ^(Note 3)
+5V	1A	11A	14A	±1%	±2%	50mV	5.05V to 5.15V
+12V	0A	5A	10A	±1%	±4%	100mV	11.6V to 12.6V
-12V	0A	0.5A	1A	±1%	±5%	150mV	-11.4V to -12.6V
+3.3V	0A	7.5A	12A	±1%	±4%	50mV	3.20V to 3.40V
+5Vsb	0A	0.75A	1.5A	±1%	±4%	100mV	4.80V to 5.20V

Total Output Power: 150W at 50°C environment temperature.

Note: 1) The maximum total combined output power on the +3.3V and +5V rails is 90W.

2) Measured by a 20MHz bandwidth limited oscilloscope and the each output is connected with a 10µF Electrolytic Capacitor and a 0.1µF Ceramic Capacitor.

3) Initial Setting Accuracy is at Input 110VAC and all output at 60% rated load.

2. Input Specification

Parameter	Conditions/Description	Min.	Nom.	Max.	Units
Input Voltage	Continuous input range.	90	115/230	264	VAC
Input Frequency	AC input.	47		63	Hz
Hold Up Time	Nominal AC Input Voltage (115VAC), rated load.	16			ms
Input Current	Nominal AC Input Voltage (115VAC/230VAC), rated load.			4/2	A
Inrush Current	Nominal AC Input Voltage (115VAC/230VAC), one cycle at 25°C.			30/60	A
Input Protect	Non-user serviceable internally located AC input line fuse.				

3. Output Specification

Parameter	Conditions/Description	Min.	Nom.	Max.	Units
Efficiency	Rated load, 115VAC. Varies with distribution of loads among output.		75		%
Minimum load			See Chart of Description		
Ripple & Noise	Rated load, 20MHz bandwidth		See Chart of Description		
Output Power	Continuous output power.		See Chart of Description		
Line Regulation	Less than ±1% at rated load with ±10% changing in input voltage.		See Chart of Description		
Load Regulation	Measured from 60% to 100% rated load and from 60% to 20% rated load (60% ±40% rated load) for each output, and others voltage setting at 60%.		See Chart of Description		
Turn-on Delay	Time required for initial output voltage stabilization	0.3		6	Sec



4. Interface Signals and Internal Protection

Parameter	Conditions/Description
Power On/Off	The power supply will be turned on when the power On/Off pin is connected to secondary GND.
Power Good Signal	When power is turned on, the power good signal will go high 100ms to 500ms after all output DC voltages are within regulation limits.
Power Fail Signal	The power fail signal will go low at least 1 mS before any of the output voltages fall below the regulation limits.
Short Circuit Protection	Fully protected against short circuit. Latch off mode upon of short circuit condition.
Over Voltage Protection	For some reason the power supply fails to control itself, the build-in over voltage protection circuit will shut down the outputs to prevent damaging external circuits. The trigger point is 7V max. at +5V. If the OVP occur, PSU cannot be recovered.
Over Temperature Protection	When the power supply operating over the temperature or over load limit, the power supply will be shut down automatically to protect itself. The protection point is at the temperature of the HS1 over 110°C. After the temperature of HS1 going down, the power supply will restart automatically.

5. Safety Approvals, EMI and EMS Specification

Parameter	Conditions/Description	Min.	Nom.	Max.	Units
Approvals	UL, UL 60950, 3rd edition CB, IEC 60950-1 TUV, EN 60950-1: 2001				UL, cUL and CB approved TUV pending
Hi-Pot	Input to output	4242			VDC
EMI	EN 55022 / CISPR 22 & FCC Part 15	B			Class
PFC	EN 61000-3-2 & EN 610003-3	D			
EMS	IEC 61000-4-2, 8KV air discharge and 6KV contact discharge	3			Level
	IEC 61000-4-3, 3V/M	3			
	IEC 61000-4-4, 2KV line & PE	3			
	IEC 61000-4-5, 2KV	3			
	IEC 61000-4-6, 10V	3			
	IEC 61000-4-8, 10A/M	3			
	IEC 61000-4-11				

6. Environment Specification

Parameter	Conditions/Description	Min.	Nom.	Max.	Units
Operating Temperature	Derate linearly above 50°C by 2.5% per °C At 100% load: to a maximum temperature of 70°C At 50% load:	0		50 70	°C
Storage Temperature		-20		+70	°C
Relative Humidity	Non-condensing.	5		95	%RH
Altitude	Operating			10K	Feet
	Non-operating			40K	

7. Mechanical Specification

Parameter	Conditions/Description
Dimension	198 (L) x 97 (W) x 40.5 (H) mm, Tolerance +/- 0.4mm.
Connector	CN1 --- AC input: 3 Positions Terminal blocks. CN2 --- DC output: 8 Positions Terminal blocks. CN3 --- Fan Connector: Molex 5045-02A or equivalent CN4 --- DC output: Molex 5045-02A or equivalent CN5 --- PS ON/OFF: Molex 5045-02A or equivalent CN6 --- UPS Connector: Molex 5273-03A with draw 1 pin or equivalent. CN7 --- PG/PF: Molex 5045-02A or equivalent



Pin Assignment	CN1	Pin	1. L	2. N	3. GND
	CN2	Pin	1. -12V	4. GND	7. +12V
			2. GND	5. +5V	8. GND
			3. 3.3V	6. +5V	
	CN3	Pin	1. +12V	2. GND	
	CN4	Pin	1. +5Vsb	2. GND	
	CN5	Pin	1. +5V	2. GND	
CN6	Pin	1. +380V	2. GND		
CN7	Pin	1. +5V	2. GND		

8. Options

Parameter	Conditions/Description	DIMENSIONS (mm)
Cable (No. 866-815H)	ATX connector, HDD connector x 2, FDD connector x 1	

Mechanical

