



200 Watt Medical Series

Desktop Type

ATM200T - □ X X X

P : C14 ← → O / P Voltage
A : C8 / C18

Green Mode

Meet CEC, DoE Level VI, Energy Star, ErP Stage 2
No Load Power Consumption Less Than 0.15W

Features :

- IEC/EN/ANSI/AAMI ES60601-1 (Edition 3.1)
- EMC : IEC60601-1-2 : 2014 (Edition 4.0)
- IEC 60950 approval
- Means of Protection: 2 X MOPP
- Touch Current : < 100µA
- 100-240VAC Universal Input
- Single Output to 200W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 2 Years Warranty

Model	O/P Voltage	O/P Current	Watt
ATM200T-□120	12.0V	16.00A	192W
ATM200T-A150	15.0V	13.00A	195W
ATM200T-□180	18.0V	11.00A	198W
ATM200T-□190	19.0V	10.50A	200W
ATM200T-□240	24.0V	8.30A	200W
ATM200T-□480	48.0V	4.20A	201W

Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	P : 2.5A-0.9A A : 2.4A-0.9A
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C8, C14, C18

Output

Load Regulation	±5% (Typical)
Ripple & Noise	1% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection
DC Cord	UL 2464 / UL 2095
Ferrite Core	No (Optional)

Safety Approvals

CB / UL / cUL / FCC / CE / TÜV SÜD Mark / PSE

Electrical

Topology	LLC
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100µA
Efficiency	Meet DoE Level VI
EMC Standards	EN55011
	EN61000-3-2,3
	EN61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH
	Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Case Dimension	L 204 x W 81 x H 42.5 (mm)
Weight	880g (Ref.)